

Evidential cognitive maps

Bingyi Kang^a, Yong Deng^{a,b,*}, Rehan Sadiq^c, Sankaran Mahadevan^b

^aSchool of Computer and Information Science, Southwest University, Chongqing 400715, China

^bSchool of Engineering, Vanderbilt University, Nashville, TN 37235, USA

^cSchool of Engineering, University of British Columbia Okanagan, 3333 University Way, Kelowna, BC, Canada V1V 1V7

ARTICLE INFO

Article history:

Received 10 November 2011

Received in revised form 6 March 2012

Accepted 3 April 2012

Available online 12 April 2012

Keywords:

Evidential cognitive maps

Evidence theory

Fuzzy cognitive maps

Data fusion

Decision making

ABSTRACT

In order to handle uncertain information, this paper proposes evidential cognitive maps (ECMs), similar to the fuzzy cognitive maps (FCMs). ECMs are uncertain-graph structures for representing causal reasoning through the combination of cognitive maps and Dempster Shafer evidence theory. The framework of ECMs is developed in detail and an application to socio-economic model is used to illustrate the application of the proposed methodology.

© 2012 Elsevier B.V. All rights reserved.

1. Introduction

The concept of fuzzy cognitive map has received special attention in recent years as a powerful tool to manipulate knowledge by imitating human reasoning and thinking. Many complex problems like fuzzy control [1–3], approximate reasoning [4–7], strategic planning [8–11], data mining [12], virtual worlds and network models [13] have been dealt with using FCMs. Especially, in the field of medical decision making [14,15], Kannappan [16] models and predicts autistic spectrum disorder using FCM, and an unsupervised non-linear Hebbian learning algorithm is applied to improve its efficiency. Papageorgiou [17] presents a novel framework for the construction of augmented FCMs based on fuzzy rule-extraction methods for decisions in medical informatics. The study extracted the available knowledge from data in the form of fuzzy rules and inserted them into the FCM, contributing to the development of a dynamic decision support system. FCM has also been investigated for risk analysis of pulmonary infections during patient admission into the hospital [18–23].

Although FCM has achieved success in many fields, there are some limitations inherent in FCM, such as lack of adequate capability to handle uncertain information and lack of enough ability to aggregate the information from different sources. Some attention has been paid to the first issue by some researchers. For example, Salmeron [24] proposes an innovative and flexible model based on

Grey Systems Theory, called fuzzy grey cognitive maps (FGCM), which can be adapted to a wide range of problems, especially in multiple meaning-based environments. Iakovidis and Papageorgiou [25] propose an approach based on cognitive maps and intuitionistic fuzzy logic, which is called intuitionistic fuzzy cognitive map (IFCM) to extend the existing FCM by considering the expert's hesitancy in the determination of the causal relations between the concepts of a domain. Similarly, after the introduction of neutrosophic logic (similar to intuitionistic fuzzy sets) by Samarandache [26], indeterminacy has been introduced into causal relationships between some of concepts of FCMs. This is a generalization of FCMs and the structure is called neutrosophic cognitive maps (NCMs) [27]. However, how to extend the ability of FCM to aggregate the information from different sources under uncertain environment is a significant question in the application of FCM and is still an open issue.

Uncertain information fusion has been studied for many years [28–41], indicating that Dempster Shafer theory (DS theory or evidence theory) is an effective framework to represent and fuse uncertain information. Therefore this paper combines FCM and evidential theory to the concept development of evidential cognitive maps that not only remains the ability to represent uncertainty but also contributes to aggregating knowledge from different sources (experts/commanders). The combination of evidence theory and FCM is shown to be a valuable approach through illustrations.

This paper is organized as follows: Section 2 briefly presents FCM and basic evidence theory and some operations of interval numbers. Section 3 develops the mathematical model of the proposed ECM concept. Section 4 describes the implementation

* Corresponding author at: School of Computer and Information Science, Southwest University, Chongqing, 400715, China.

E-mail address: ydeng@swu.edu.cn (Y. Deng).

of ECM. Section 5 briefly presents qualitative comparison of ECM with FCM and NCM. An application of ECM to socio-economic model is presented in Section 6.

2. Preliminaries

In this section, we briefly introduce FCM and evidence theory.

2.1. FCM

Political scientist Robert Axelrod [42] introduced cognitive maps in the 1970's for representing social scientific knowledge. Fuzzy cognitive map (FCM), an extension of the cognitive map, is a causal description in order to model the behavior of the system [43]. FCM is an interactive structure of concepts, each of which interacts with the rest showing the dynamics and different aspects of the behavior of the system. Human experience and knowledge of the operation of complex systems are embedded in FCM, i.e., knowledge gained about the operation of the system and its behavior under different circumstances by human experts.

FCM consists of nodes (concepts, agents) and weighted arcs (connection, edge), which are graphically illustrated as signed weighted graph with optional feedback loops. Nodes on the graph represent concepts describing behavioral characteristics of the system. Concepts can be inputs, outputs, variables, states, events, actions, goals, and trends of the system. Signed weighted arcs represent causal relationships (cause and effect) that exist among concepts.

Fig. 1 illustrates a simple FCM consisting of six concepts C_i ($i = 1, \dots, 6$). The value of C_i is denoted by A_i ($i = 1, \dots, 6$), where A_i is mapped in the interval $[0, 1]$. Weight $\omega_{ij} \in [-1, 1]$ represents the causal relationship between concept i and concept j , where a negative sign represents inverse causation. This scheme may give rise to the following three types of interactions:

- (1) $\omega_{ij} > 0$ indicates a positive causality, where an increase in the value of the i th concept causes an increase in the value of the j th concept;
- (2) $\omega_{ij} < 0$ indicates a negative causality, where an increase in the value of the i th concept causes an decrease in the value of the j th concept;
- (3) $\omega_{ij} = 0$ indicates that there is no causal relationship between the i th concept and the j th concept.




Fig. 1. The structural diagram of fuzzy cognitive map.

The edge matrix of six concept fuzzy cognitive map is denoted as in Eq. (1).

$$W = \begin{matrix} & \begin{matrix} C_1 & C_2 & C_3 & C_4 & C_5 & C_6 \end{matrix} \\ \begin{matrix} C_1 \\ C_2 \\ C_3 \\ C_4 \\ C_5 \\ C_6 \end{matrix} & \begin{pmatrix} 0 & \omega_{12} & 0 & \omega_{14} & 0 & \omega_{16} \\ 0 & 0 & \omega_{23} & \omega_{24} & 0 & 0 \\ 0 & \omega_{32} & 0 & 0 & \omega_{35} & \omega_{36} \\ 0 & \omega_{42} & \omega_{43} & 0 & 0 & \omega_{46} \\ 0 & \omega_{52} & 0 & \omega_{54} & 0 & \omega_{56} \\ \omega_{61} & 0 & 0 & 0 & 0 & 0 \end{pmatrix} \end{matrix} \quad (1)$$

Kosko [43] proposed a rule to calculate the value of each concept based on the influence of the interconnected concepts, where the content of the following function is normalized in the interval $[-1, 1]$:

$$A_j^t = f \left(k_1 \sum_{\substack{i=1 \\ i \neq j}}^n A_i^{t-1} \omega_{ij} + k_2 A_j^{t-1} \right) \quad 0 \leq k_1 \leq 1 \quad 0 \leq k_2 \leq 1 \quad (2)$$

where A_j^t is the normalized ($A_j^t \in [0, 1]$) value (a.k.a activation level) of concept C_j at time step t , and $f(x)$ is a threshold function. Generally, a sigmoidal function $f(x) = \frac{1}{1+e^{-\lambda x}}$ is used to constrain the value of $f(x)$ in the interval $[0, 1]$, where $\lambda > 0$ determines the steepness of $f(x)$. The coefficient k_1 expresses the influence of interconnected concepts in the configuration of the new value A_i of concept C_i . For example, in Fig. 1, the concept C_6 receives inputs from concepts C_1, C_3, C_4 , and C_5 . If experts perceive that C_4 and C_5 interact in such a way that both are fully participating in impacting C_6 then the k_1 associated with them will be closer to 1. Similarly, k_2 accounts for the importance of C_6 being at its activation level in the previous time step. The selection of coefficients k_1 and k_2 depends on the nature and type of each concept, and may differ from concept to concept.

2.2. Dempster–Shafer (DS) theory of evidence

The DS theory of evidence, which was first proposed by Dempster [28] and then developed by Shafer [31], is regarded as a generalization of the Bayesian theory of probability. Due to its ability to handle uncertainty or imprecision embedded in the evidence, the DS theory has been increasingly applied in recent years [44–47, 41, 48–52], and applied to multiple attribute decision analysis problems [53–57].

The introduction of DS theory are briefly summarized as following:

- (1) “Frame of discernment” [31]:
Let $\Theta = \{H_1, H_2, \dots, H_N\}$ be a finite set of n elements, and $P(\Theta)$ denote the power set composed of 2^N elements of Θ .
$$P(\Theta) = \{\emptyset, \{H_1\}, \{H_2\}, \dots, \{H_N\}, \{H_1 \cup H_2\}, \{H_1 \cup H_3\}, \dots, \Theta\} \quad (3)$$
- (2) “Basic probability assignment (BPA)” [31]:
The BPA function is defined as a mapping of the power set $P(\Theta)$ to a number between 0 and 1.
$$m : P(\Theta) \rightarrow [0, 1] \quad (4)$$

and which satisfies the following conditions:

$$m(\emptyset) = 0, \quad \sum_{A \subseteq P(\Theta)} m(A) = 1 \quad (5)$$

The mass $m(A)$ represents how strongly the evidence supports A .




Fig. 2. The relation between Bel and Pl.

(3) “Belief and plausibility functions” [31]:
The belief function Bel is defined as

$$Bel : P(\Theta) \rightarrow [0, 1] \text{ and } Bel(A) = \sum_{B \subseteq A} m(B) \quad (6)$$

and the plausibility function Pl is defined as

$$Pl : P(\Theta) \rightarrow [0, 1] \text{ and } Pl(A) = 1 - Bel(\bar{A}) = \sum_{B \cap A \neq \emptyset} m(B) \quad (7)$$

$Bel(A)$ and $Pl(A)$ are the lower limit and the upper limit, respectively, of the belief level of hypothesis A which is illustrated in Fig. 2. Both imprecision and uncertainty can be represented by them.

(4) “Dempster’s combination rule”:

Two bodies of evidence X and Y regarding Θ can be used to calculate the belief level for some new hypothesis C as follows:

The measure of conflict K is given as

$$K = \sum_{X \cap Y = \emptyset, \forall X, Y \subseteq \Theta} m_i(X) \times m_j(Y) \quad (8)$$

and the mass function after combination is

$$m(C) = m_i(X) \oplus m_j(Y) = \begin{cases} 0, & \text{if } X \cap Y = \emptyset, \\ \frac{\sum_{X \cap Y = C, \forall X, Y \subseteq \Theta} m_i(X) \times m_j(Y)}{1 - K}, & \text{if } X \cap Y \neq \emptyset. \end{cases} \quad (9)$$

2.3. Basic operations of interval numbers

Let \tilde{A}, \tilde{B} be two interval numbers, $\tilde{A} = [A_l, A_u], \tilde{B} = [B_l, B_u]$.

(1) The representation of the addition operation \oplus on interval numbers \tilde{A} and \tilde{B} can be defined as

$$\tilde{A} \oplus \tilde{B} = [A_l + B_l, A_u + B_u] \quad (10)$$

Note that $\oplus_1^n(\tilde{A}_i) = \tilde{A}_1 \oplus \tilde{A}_2 \oplus \dots \oplus \tilde{A}_n$.

(2) The representation of the multiplication operation \otimes on interval numbers \tilde{A} and \tilde{B} can be defined as

$$\tilde{A} \otimes \tilde{B} = [Z_l, Z_u] \quad (11)$$

such that

$$Z_l = \min\{A_l B_l, A_l B_u, A_u B_l, A_u B_u\}$$

$$Z_u = \max\{A_l B_l, A_l B_u, A_u B_l, A_u B_u\}$$

where min and max are the minimum and maximum of the denoted values.

3. Evidential cognitive map (ECM)

ECM is also a directed graph with feedback, consisting of nodes and weighted arcs. Nodes of the graph stand for the concepts that are used to describe the behavior of the system and they are connected by weighted arcs representing the causal relationships that exist between the concepts. Each concept \tilde{C}_i is characterized by an interval \tilde{A}_i that represents its value, and it results from the transformation of the fuzzy value of the system variable. In this way, the representation of the concept is more flexible than the representation of the concept in FCM that uses crisp numbers.

3.1. Edge weight of the cognitive map

In a cognitive map, experts’ opinions are reflected by the estimate of the degree of causation between nodes in the referred concept set, namely weight estimate. Each expert’s estimate of some causal relation can be regarded as evidence. Generally, due to the complexity of the relations between concepts and limitation of knowledge and experience of experts, the causal relation of two concepts could be described by the following four cases in the evidence theory:

- (1) Negative causal relation, which can be described as $m\{-1\}$, where an increase in the value of the i th concept causes a decrease in the value of the j th concept.
- (2) Positive causal relation, which can be described as $m\{+1\}$, where an increase in the value of the i th concept causes an increase in the value of the j th concept.
- (3) No causal relation between the i th concept and the j th concept, which can be described as $m\{0\}$.
- (4) No idea or abstaining from voting, which can be described as $m\{-1, 0, 1\}$.

Hence, the combined influence from concept i th to concept j th can be described as

$$BPA_{ij} = \begin{pmatrix} m\{-1\} = a \\ m\{1\} = b \\ m\{0\} = c \\ m\{-1, 0, 1\} = 1 - a - b - c \end{pmatrix} \quad (12)$$

such that $a \geq 0, b \geq 0, c \geq 0, 1 - a - b - c \geq 0$.

With this representation, the uncertainty of the causal relation between two concepts is more clearly described and handled compared to the frame of FCM. The idea of evidential cognitive map is illustrated by Fig. 3, and the weights are shown as in Eq. (13).

$$W = \begin{matrix} \tilde{C}_1 & \tilde{C}_2 & \tilde{C}_3 & \tilde{C}_4 & \tilde{C}_5 & \tilde{C}_6 \\ \tilde{C}_1 & \begin{pmatrix} 0 & BPA_{12} & 0 & BPA_{14} & 0 \\ 0 & 0 & BPA_{23} & BPA_{24} & 0 \\ 0 & BPA_{32} & 0 & 0 & BPA_{35} \\ 0 & BPA_{42} & BPA_{43} & 0 & 0 \\ 0 & BPA_{52} & 0 & BPA_{54} & 0 \\ BPA_{61} & 0 & 0 & 0 & 0 \end{pmatrix} & BPA_{16} \\ \tilde{C}_2 & & 0 \\ \tilde{C}_3 & & & BPA_{36} \\ \tilde{C}_4 & & & & BPA_{46} \\ \tilde{C}_5 & & & & & BPA_{56} \\ \tilde{C}_6 & & & & & & 0 \end{matrix} \quad (13)$$

3.2. Aggregate knowledge under conflict environment

In the process of collection of knowledge, the experts’ opinions may be inconsistent with each other. How to combine the knowledge to reach consensus is a critical problem. In this paper, the method of combining belief functions based on distance of evidence proposed by Deng et al. [58] is applied. The main process is as follows:

Suppose the distance between two bodies of evidence (R_i, m_i) and (R_j, m_j) can be calculated by the algorithm in Ref. [59] and is denoted as $d(m_i, m_j)$.

$$d(m_i, m_j) = \sqrt{\frac{1}{2}(\bar{m}_i - \bar{m}_j)^T \bar{D}(\bar{m}_i - \bar{m}_j)} \quad (14)$$

such that \bar{D} is a matrix ($2^N \times 2^N$), and $D(A, B) = \frac{|A \cap B|}{|A \cup B|}$.

The similarity measure Sim_{ij} between the two bodies of evidence (R_i, m_i) and (R_j, m_j) is defined as:

$$Sim(m_i, m_j) = 1 - d(m_i, m_j) \quad (15)$$




Fig. 3. The structural diagram of evidential cognitive map.

Suppose the number of bodies of evidence is k . After all the degrees of similarity between the bodies of evidence are obtained, we can construct a *similarity measure matrix* (SMM), which gives us insight into the agreement between the bodies of evidence.

$$SMM = \begin{pmatrix} 1 & S_{12} & \cdots & S_{1j} & \cdots & S_{1k} \\ \vdots & \vdots & & \vdots & & \vdots \\ S_{i1} & S_{i2} & & S_{ij} & & S_{ik} \\ \vdots & \vdots & & \vdots & & \vdots \\ S_{k1} & S_{k2} & & S_{kj} & & 1 \end{pmatrix} \quad (16)$$

The support degree of the body of evidence $(R_i, m_i)(i = 1, 2, \dots, k)$ is defined as:

$$Sup(m_i) = \sum_{\substack{j=1 \\ j \neq i}}^k Sim(m_i, m_j) \quad (17)$$

The credibility degree Crd_i of the body of evidence $(R_i, m_i)(i = 1, 2, \dots, k)$ is defined as:

$$Crd_i = \frac{Sup(m_i)}{\sum_{i=1}^k Sup(m_i)} \quad (18)$$

It can be easily seen that $\sum_{i=1}^n Crd_i = 1$, thus, the credibility degree is actually a weight, which shows the relative importance of the collected evidence.

If the maximum of the credibility degree ($MaxCrd_i$) of the body of evidence is 1, which can be the discounting coefficient for the i th evidence, and the discounting coefficient of the body of evidence can be defined as:

$$\alpha_i = \frac{Crd_i}{MaxCrd_i}, (i = 1, \dots, k) \quad (19)$$

If a source of evidence provides a mass function m which has probability α of reliability, then the discounted belief m' on Θ is defined as [28]:

$$m'(A) = \alpha m(A), \quad \forall A \subset \Theta, A \neq \Theta \quad (20)$$

$$m'(\Theta) = 1 - \alpha + \alpha m(\Theta) \quad (21)$$

All mass functions are discounted by α , the discounting coefficient. Then the modified (discounted) evidence can be combined with the classical combination rule Eq. (9) to get the aggregated result.

3.3. Transformation using the belief function and plausibility function

The next step is to estimate each connection weight of the evidential cognitive map in Fig. 3. Take any BPA_{ij} for example. It can be denoted explicitly by

$$\begin{aligned} m\{-1\} &= a \\ m\{1\} &= b \\ m\{0\} &= c \\ m\{-1, 0, 1\} &= 1 - a - b - c \end{aligned} \quad (22)$$

such that $a \geq 0, b \geq 0, c \geq 0, 1 - a - b - c \geq 0$. According to Eq. (6),

$$Bel\{-1\} = m\{-1\} = a \quad (23)$$

$$Pl\{-1\} = m\{-1\} + m\{-1, 0, 1\} = 1 - b - c \quad (24)$$

Hence, the possibility of the positive casual relation $P\{-1\}$ is denoted as

$$P\{-1\} = [Bel\{-1\}, Pl\{-1\}] = [a, 1 - b - c] \quad (25)$$

Similarly, $P\{1\} = [b, 1 - a - c]$, $P\{0\} = [c, 1 - a - b]$. And the connection weight from \tilde{C}_1 and \tilde{C}_4 can be calculated as follows (Here the 4th influence is ignored since it is abstention from voting):

$$\begin{aligned} \tilde{\omega}_{ij} &= P\{1\} \times 1 \oplus P\{0\} \times 0 \oplus P\{-1\} \times (-1) \\ &= 1 * [b, 1 - a - c] \oplus 0 * [a, 1 - b - c] \oplus (-1) * [a, 1 - b - c] \\ &= [b, 1 - a - c] \oplus [-1 + b + c, -a] = [2b + c - 1, 1 - 2a - c] \end{aligned} \quad (26)$$

$$W = \begin{matrix} \tilde{C}_1 & \tilde{C}_2 & \tilde{C}_3 & \tilde{C}_4 & \tilde{C}_5 & \tilde{C}_6 \\ \tilde{C}_1 & 0 & \tilde{\omega}_{12} & 0 & \tilde{\omega}_{14} & 0 & \tilde{\omega}_{16} \\ \tilde{C}_2 & 0 & 0 & \tilde{\omega}_{23} & \tilde{\omega}_{24} & 0 & 0 \\ \tilde{C}_3 & 0 & \tilde{\omega}_{32} & 0 & 0 & \tilde{\omega}_{35} & \tilde{\omega}_{36} \\ \tilde{C}_4 & 0 & \tilde{\omega}_{42} & \tilde{\omega}_{43} & 0 & 0 & \tilde{\omega}_{46} \\ \tilde{C}_5 & 0 & \tilde{\omega}_{52} & 0 & \tilde{\omega}_{54} & 0 & \tilde{\omega}_{56} \\ \tilde{C}_6 & \tilde{\omega}_{61} & 0 & 0 & 0 & 0 & 0 \end{matrix} \quad (27)$$

3.4. ECM dynamics

At each simulation step, the value \tilde{A}_i of a concept \tilde{C}_i is calculated by computing the influence of the interconnected concepts \tilde{C}_j 's on the specific concept \tilde{C}_i following the calculation rule:

$$\tilde{A}_j^t = f \left(\begin{matrix} k_1 \bigoplus_{i=1}^n (A_i^{t-1} \otimes \tilde{\omega}_{ij}) \oplus k_2 A_j^{t-1} \end{matrix} \right) \quad 0 \leq k_1 \leq 1 \quad 0 \leq k_2 \leq 1 \quad (28)$$

where \tilde{A}_j^t is the value of concept \tilde{C}_j at simulation step t , \tilde{A}_j^{t-1} is the value of concept \tilde{C}_j at simulation step $t - 1$. The meaning of k_1 and k_2 here is the same as meaning of k_1 and k_2 in FCM. $\tilde{\omega}_{ij}$ is the weight of the interconnection from concept \tilde{C}_i to concept \tilde{C}_j and f is nonlinear mapping function as

$$f(\tilde{X}) = \frac{1}{1 + e^{-\lambda \tilde{X}}} \quad (29)$$

where \tilde{X} is an interval number and λ is a parameter determining its steepness. The output of f is also an interval number. It can approximately handle the uncertain information from concepts and connection weights. The meaning of f is illustrated in Fig. 4 ($x > 0$).

4. Application framework of ECMs

The Framework of ECM is shown as Fig. 5, and its application is detailed as follows:

4.1. Knowledge acquisition

Suppose we have m experts, and they are divided into n groups according to their knowledge and background. For each group, the relationship (or the edge weight) between the concepts (or the nodes) is decided by voting. For example, may there are ten experts to evaluate the relation from the i th concept to j th concept, and six of them think that it is positive, one of them thinks that it is negative, one of them has no idea, and others are abstain from voting. Hence, using evidence theory, the relation between concept \tilde{C}_i and concept \tilde{C}_j is described as: $m_1\{-1\} = 0.1$; $m_1\{0\} = 0.1$; $m_1\{+1\} =$

0.6 ; $m_1\{-1, 0, +1\} = 0.2$. This evidence can also be given by a single expert/commander directly.

4.2. Knowledge aggregation

This step allows the aggregation of knowledge acquired from various sources to develop a comprehensive ECM, which will represent the understanding of the experts about the special issue. The comprehensive ECM combines partial ECMs from inner groups and outer groups. The aggregation of knowledge from inner groups is for the opinions of the experts of each group and the aggregation of knowledge from outer groups is for the edges of the partial ECMs.

In this part, a critical problem is how to deal with the conflicting evidences since the opinions from different experts are not always consistent. The method dealing with conflicting evidence in evidence theory is mature, here the method of combing conflicting evidence proposed by Deng [58] is applied here.

4.3. Training ECM

ECM is a dynamic system, and the procedure is described in Algorithm 1 in detail. After converting the evidence into interval numbers with the belief and plausibility functions. The state vector can be handled easily, which has more flexibility to deal with uncertain and fuzzy information when compared to the classical fuzzy cognitive maps. Whether the dynamic is reaches equilibrium, the paper [60] has provided some inspiration for the interpretation of the condition.




Fig. 4. The nonlinear mapping function.




Fig. 5. Framework of ECM.

Algorithm 1. The convergent procedure of state vector of ECMs

Input: the initial state vector of nodes, $X_i = [A_1, A_2, \dots, A_n]$;

the matrix of edge weight $W_{n \times n}$;

Output: the equilibrium state vector of nodes,

$X_e = [A_1, A_2, \dots, A_n]$;

```

1 Temp = [] = Xi;
2 While not satisfy the condition do
3 Xi = Temp;
4 for j = 1; j ≤ n; do
5 sum_l = 0;
6 sum_u = 0;
7 for j = 1; j ≤ n; do
8 if i ≠ j then
9 a = Xi(i, 1) * W(i, j, 1);
10 b = Xi(i, 1) * W(i, j, 2);
11 c = Xi(i, 2) * W(i, j, 1);
12 d = Xi(i, 2) * W(i, j, 2);
13 sum_l = sum_l + min{a, b, c, d};
14 sum_u = sum_u + max{a, b, c, d};
15 end
16 end
17 sum_l = sum_l + Xi(j, 1);
18 sum_u = sum_u + Xi(j, 2);
19 Temp(j,1) = function(sum_l);
20 Temp(j,2) = function(sum_u);
21 if Temp(j, 1) ≤ 0.5 then
22 Temp(j, 1) = 0;
23 Temp(j, 2) = 0;
24 end
25 end
26 Xe = Temp;
27 end
28 return Xe;
    
```

4.4. Interpreting ECM

The outcome of an ECM is in the form of concepts being “activated” at different levels after reaching equilibrium. The interpretation of these concepts will determine the judgement for a given scenario.

5. Qualitative comparison with FCM and NCM

Here (in ECM) we use the fact that between any two concepts/ nodes the existing relation may be an indeterminate (as) in reality, FCM do not reflect the notion of indeterminacy. Some differences between ECM and FCM are listed as follows:

Table 1
Experts' knowledge in group 1 (values of aggregated knowledge are shown in bold).

	\tilde{C}_1	\tilde{C}_3	\tilde{C}_5
\tilde{C}_1	-	E1: (0.7, 0.1, 0.0, 0.2) E2: (0.8, 0.0, 0.0, 0.2) E3: (0.2, 0.5, 0.1, 0.2) E123: (0.8782, 0.0759, 0.0076, 0.0383)	E1: (0.1, 0.6, 0.1, 0.3) E2: (0.3, 0.3, 0.0, 0.4) E3: (0.1, 0.5, 0.2, 0.2) E123: (0.0980, 0.7978, 0.0699, 0.0342)
\tilde{C}_3	-	-	E1: (0.6, 0.1, 0.1, 0.2) E2: (0.7, 0.1, 0.0, 0.2) E3: (0.3, 0.5, 0.0, 0.2) E123: (0.8369, 0.1225, 0.0135, 0.0271)
\tilde{C}_5	-	-	-

Table 2
Experts' knowledge in group 2 (values of aggregated knowledge are shown in bold).

	\tilde{C}_1	\tilde{C}_2	\tilde{C}_3	\tilde{C}_4
\tilde{C}_1	-	-	E1: (0.5, 0.1, 0.1, 0.2) E2: (0.7, 0.1, 0.1, 0.1) E3: (0.3, 0.6, 0.0, 0.1) E123: (0.7851, 0.1575, 0.0313, 0.0260)	-
\tilde{C}_2	-	-	-	E1: (0.5, 0.1, 0.1, 0.2) E2: (0.4, 0.1, 0.1, 0.1) E3: (0.3, 0.0, 0.2, 0.5) E123: (0.7088, 0.0649, 0.1263, 0.1001)
\tilde{C}_3	-	E1: (0.5, 0.1, 0.1, 0.2) E2: (0.5, 0.2, 0.1, 0.2) E3: (0.7, 0.0, 0.0, 0.3) E123: (0.8848, 0.0520, 0.0313, 0.0319)	-	-
\tilde{C}_4	E1: (0.7, 0.1, 0.0, 0.2) E2: (0.2, 0.5, 0.1, 0.2) E3: (0.6, 0.1, 0.0, 0.3) E123: (0.8055, 0.1478, 0.0106, 0.0362)	E1: (0.1, 0.5, 0.2, 0.2) E2: (0.1, 0.5, 0.2, 0.2) E3: (0.0, 0.7, 0.0, 0.3) E123: (0.0295, 0.8763, 0.0707, 0.0236)	-	-

Table 3
Experts' knowledge in group 3 (values of aggregated knowledge are shown in bold).

	\tilde{C}_1	\tilde{C}_4	\tilde{C}_5
\tilde{C}_1	-	-	E1: (0.1, 0.7, 0.1, 0.1) E2: (0.0, 0.6, 0.0, 0.4) E3: (0.5, 0.2, 0.2, 0.1) E123: (0.1090, 0.8078, 0.0585, 0.0248)
\tilde{C}_4	E1: (0.6, 0.1, 0.1, 0.2) E2: (0.4, 0.2, 0.2, 0.2) E3: (0.5, 0.1, 0.2, 0.2) E123: (0.8146, 0.0681, 0.0984, 0.0189)	-	-
\tilde{C}_5	-	E1: (0.5, 0.4, 0.0, 0.1) E2: (0.2, 0.6, 0.0, 0.2) E3: (0.1, 0.7, 0.0, 0.2) E123: (0.1346, 0.8600, 0.0000, 0.0054)	-

- (1) FCM measures the existence of causal relation between two concepts using crisp number between -1 and 1 and if no relation exists it is denoted by 0 . ECM measures not only the existence or absence of causal relations between two concepts but also give representation to the indeterminacy of the relation.
- (2) Because ECM measures the indeterminacy, the expert of the model can give due and careful representation while implementing the results of the model.
- (3) Being able to aggregate multiple sources and conflicting information is an important advantage in ECM.

The advantage of ECM compared with NCM can be listed as follows:

- (1) More accurate representation of knowledge and dynamics of system. In NCM, every edge is weighted with a number in the set $\{-1, 0, 1\}$, and if there is a hesitating decision, I , which is a symbol, is directly used to represent the indeterminacy, but in ECM, every edge is weighted with belief and plausibility dimension using BPA $\{m\{-1\}, m\{0\}, m\{1\}, m\{-1, 0, 1\}\}$, where $m\{-1\}, m\{0\}, m\{1\}, m\{-1, 0, 1\}$ all belong to the interval $[0, 1]$ and they are all crisp number, and there is no symbolic computation. Therefore, it is a more accurate representation and can describe the behavior of the system more accurately.
- (2) Being able to aggregate multiple, conflicting information using evidence theory is an important advantage in ECM.

6. An application of ECM to a socio-economic model

This section illustrates the application of the proposed method to a socio-economic model. It is constructed with Population, Crime, Economic condition, Poverty, and Unemployment as nodes or concepts. Our purpose is to evaluate the trend of factors changing with any one factor using ECM.

First, the structure of ECM should be established using several sources of partial knowledge. All the available experts are divided into three groups (group1, group2, and group3), and the opinions are provided in Tables 1–3. They can be described as Figs. 6–8 accordingly.

Next, the opinions from different experts and the partial ECMs are combined together considering the conflict in the evidence. (See Table 4 and Fig. 9).

Take group1 for example; The relationships between \tilde{C}_1 and \tilde{C}_3 is provided by three evidences (Evidence1 (E1), Evidence2 (E2) and Evidence3 (E3)) as follows:




Fig. 6. Partial ECM from group 1.




Fig. 7. Partial ECM from group 2.




Fig. 8. Partial ECM from group 3.




Fig. 9. The aggregation of all three partial ECMs from 3 groups.

$$\begin{aligned}
 E1 : m_1\{-1\} &= 0.7; m_1\{1\} = 0.1; m_1\{0\} = 0.0; m_1\{-1, 1, 0\} = 0.2; \\
 E2 : m_2\{-1\} &= 0.8; m_2\{1\} = 0.0; m_2\{0\} = 0.0; m_2\{-1, 1, 0\} = 0.2; \\
 E3 : m_3\{-1\} &= 0.2; m_3\{1\} = 0.5; m_3\{0\} = 0.1; m_3\{-1, 1, 0\} = 0.2;
 \end{aligned}$$

It is easy to conclude that Evidence3 is not consistent with Evidence1 and Evidence2. The combination with evidential distance is applied here, and the process is as follows:

- (1) The distance matrix of the evidences is

$$d = \begin{bmatrix} 0.00 & 0.02 & 0.42 \\ 0.02 & 0.00 & 0.62 \\ 0.42 & 0.62 & 0.00 \end{bmatrix}$$

Table 4
Aggregation of experts' knowledge from 3 groups (values of aggregated knowledge are shown in bold).

\tilde{C}_1	\tilde{C}_2	\tilde{C}_3	\tilde{C}_4	\tilde{C}_5
\tilde{C}_1 -	-	E1: (0.8782, 0.0759, 0.0076, 0.0383) E2: (0.7851, 0.1575, 0.0313, 0.0260) E12: (0.9703, 0.0261, 0.0021, 0.0013)	-	E1: (0.0980, 0.7978, 0.0699, 0.0342) E2: (0.1090, 0.8078, 0.0585, 0.0248) E12: (0.0235, 0.9644, 0.0109, 0.0012)
\tilde{C}_2 -	-	-	E1: (0.7088, 0.0649, 0.1263, 0.1001)	-
\tilde{C}_3 -	E1: (0.8848, 0.0520, 0.0313, 0.0319)	-	-	E1: (0.8369, 0.1225, 0.0135, 0.0271)
\tilde{C}_4 E1: (0.8055, 0.1478, 0.0106, 0.0362) E2: (0.8146, 0.0681, 0.0984, 0.0189) E12: (0.9713, 0.0212, 0.0067, 0.0009)	E1: (0.0295, 0.8763, 0.0707, 0.0236)	-	-	-
\tilde{C}_5 -	-	-	E1: (0.1346, 0.8600, 0.0000, 0.0054)	-

(2) The similarity matrix of the evidences is

$$SMM = \begin{bmatrix} 1.00 & 0.98 & 0.58 \\ 0.98 & 1.00 & 0.38 \\ 0.58 & 0.38 & 1.00 \end{bmatrix}$$

(3) The credibility degree of the evidences is

$$Cred = [0.3721, 0.3430, 0.2849]$$

(4) The discounting coefficient is

$$\alpha = [1.0000, 0.9219, 0.7656]$$

(5) Now we combine the three evidences using DS theory.

$$E12 : m_1\{-1\} = 0.9150; m_1\{1\} = 0.0283;$$

$$m_1\{0\} = 0.0; m_1\{-1, 1, 0\} = 0.0567;$$

$$E123 : m_1\{-1\} = 0.8782; m_1\{1\} = 0.0759;$$

$$m_1\{0\} = 0.0076; m_1\{-1, 1, 0\} = 0.0383;$$

Then, the partial ECMs can be combined with each other in a similar way. Taking Figs. 6 and 7 for example, the shared edge is from concept \tilde{C}_1 to \tilde{C}_3 , and the result of combination is shown in Tables 4 and 5.

Let $A^0 = [\tilde{A}_1^0, \tilde{A}_2^0, \tilde{A}_3^0, \tilde{A}_4^0, \tilde{A}_5^0]$ ($A_1^0 = [0.9, 1], \tilde{A}_i^0 = [0, 0], i = 2, \dots, 5$) be an initial vector state, and let $k_1 = 1$ and $k_2 = 1$. Let the sigmoidal function with $\lambda = 1$ be used as a threshold function. Figs. 10–12 represent the results of Eq. (28) simulated iteratively thirty times.

Table 5
Aggregation of experts' knowledge in 3 groups (values shown in bold are transformed using the belief function and plausibility function).

\tilde{C}_1	\tilde{C}_2	\tilde{C}_3	\tilde{C}_4	\tilde{C}_5
\tilde{C}_1	[0.0000, 0.0000]	[- 0.9457 , - 0.9427]	[0.0000, 0.0000]	[0.9397 , 0.9421]
\tilde{C}_2	[0.0000, 0.0000]	[0.0000, 0.0000]	[- 0.7439 , - 0.5439]	[0.0000, 0.0000]
\tilde{C}_3	[0.0000, 0.0000]	[- 0.8647 , - 0.8009]	[0.0000, 0.0000]	[- 0.7415 , - 0.6873]
\tilde{C}_4	[- 0.9509 , - 0.9493]	[0.8233 , 0.8703]	[0.0000, 0.0000]	[0.0000, 0.0000]
\tilde{C}_5	[0.0000, 0.0000]	[0.0000, 0.0000]	[0.7200 , 0.7308]	[0.0000, 0.0000]




Fig. 10. Results of ECM simulations (Trend of lower bound of each concept value).

It can be seen that the ECM reaches an equilibrium state approximately after 11 iterations. The values of the concepts reach an equilibrium state vector $\tilde{A}^{11} = [\tilde{A}_1^{11}, \tilde{A}_2^{11}, \tilde{A}_3^{11}, \tilde{A}_4^{11}, \tilde{A}_5^{11}]$. (See Table 6).

Once the ECM reaches equilibrium, the activation values provide the “triggering” or “firing” strength of those concepts for a given scenario. Generally, when the FCM reaches equilibrium, the activation levels are transformed back to the corresponding values. These activation levels may be interpreted quantitatively or qualitatively. For example, the ECM shown in Fig. 11 reaches an equilibrium state vector $A_{mean}^{11} = [0.0000, 0.7929, 0.0000, 0.6488, 0.6591]$, which implies that, concept \tilde{C}_2 , for example, is 79.29% (fired) of its maximum normalized value. And the whole procedure can be interpreted as a process of inference. The result can be “When the population is initially triggering, the rate of crime is increasing, the poverty is more serious, and the economic condition (volume of economic) may be improved; the population is decreasing gradually at the same time”.




Fig. 11. Results of ECM simulations (Trend of mean value of each concept value).




Fig. 12. Results of ECM simulations (Trend of upper bound of each concept value).

Table 6
Equilibrium values of the concepts.

Item	\tilde{C}_1	\tilde{C}_2	\tilde{C}_3	\tilde{C}_4	\tilde{C}_5
A^0	[0.9000, 0.1000] 0.9500	[0.0000, 0.0000] 0.0000	[0.0000, 0.0000] 0.0000	[0.0000, 0.0000] 0.0000	[0.0000, 0.0000] 0.0000
A^1	[0.7109, 0.7311] 0.9500	[0.0000, 0.0000] 0.0000	[0.0000, 0.0000] 0.0000	[0.0000, 0.0000] 0.0000	[0.6997, 0.7195] 0.0000
...
A^{11}	[0.0000, 0.0000] 0.0000	[0.7856, 0.8002] 0.7929	[0.0000, 0.0000] 0.0000	[0.6230, 0.6746] 0.6488	[0.6591, 0.6591] 0.6591
A^{12}	[0.0000, 0.0000] 0.0000	[0.7856, 0.8002] 0.7929	[0.0000, 0.0000] 0.0000	[0.6230, 0.6746] 0.6488	[0.6591, 0.6591] 0.6591

7. Conclusions

Evidential cognitive maps (ECMs) are uncertain-graph structures for representing causal reasoning. They can be considered as the exploration of cognitive maps (CMs) and fuzzy cognitive maps (FCMs). ECMs can not only deal with the uncertain information but can also handle the fuzzy information with the advantage of evidence theory, and can be used in many applications involving decision making and uncertain reasoning. The framework of ECMs is developed in this paper and a simple application is shown to illustrate the implementation. Future work needs to enhance the learning ability of ECMs to handle problems in recognition and classification.

Acknowledgments

This paper presents results of an on-going research, which is funded by Canada NSERC discovery grant. The work is also partially supported by National Natural Science Foundation of China, Grant Nos. 60874105, 60904099, 61174022, Chongqing Natural Science Foundation for Distinguished Young Scientists, Grant Nos. CSCT, 2010BA2003, Program for New Century Excellent Talents in University, Grant No. NCET-08-0345, Shanghai Rising-Star Program Grant No. 09QA1402900, the Chenxing Scholarship Youth Found of Shanghai Jiao Tong University Grant No. T241460612, Doctor Funding of Southwest University Grant No. SWU110021. The first author thanks for the Scientific & Technological Innovation Fund of School of Computer and Information Science of Southwest University.

References

- [1] C.D. Stylios, P.P. Groumos, Fuzzy cognitive maps: a model for intelligent supervisory control systems, *Computers in Industry* 39 (1999) 229–238.
- [2] S. Lee, I. Han, Fuzzy cognitive map for the design of edi controls, *Information & Management* 37 (2000) 37–50.
- [3] J. Gonzalez, L. Aguilar, O. Castillo, A cognitive map and fuzzy inference engine model for online design and self fine-tuning of fuzzy logic controllers, *International Journal of Intelligent Systems* 24 (2009) 1134–1173.
- [4] C. Miao, Q. Yang, H. Fang, A. Goh, A cognitive approach for agent-based personalized recommendation, *Knowledge-Based Systems* 20 (2007) 397–405.
- [5] M.S. Khan, M. Quaddus, Group decision support using fuzzy cognitive maps for causal reasoning, *Group Decision and Negotiation* 13 (2004) 463–480.
- [6] A. Konar, U.K. Chakraborty, Reasoning and unsupervised learning in a fuzzy cognitive map, *Information Sciences* 170 (2005) 419–441.
- [7] C. Miao, A. Goh, Y. Miao, Z. Yang, Agent that models, reasons and makes decisions, *Knowledge-Based Systems* 15 (2002) 203–211.
- [8] J. Salmeron, Augmented fuzzy cognitive maps for modelling lms critical success factors, *Knowledge-Based Systems* 22 (2009) 275–278.
- [9] L. Rodriguez-Repiso, R. Setch, J.L. Salmeron, Modelling it projects success with fuzzy cognitive maps, *Expert Systems with Applications* 32 (2007) 543–559.
- [10] P. Beena, R. Ganguli, Structural damage detection using fuzzy cognitive maps and hebbian learning, *Applied Soft Computing* 11 (2011) 1014–1020.
- [11] E. Papageorgiou, A. Markinos, T. Gemtos, Fuzzy cognitive map based approach for predicting yield in cotton crop production as a basis for decision support system in precision agriculture application, *Applied Soft Computing* 11 (2009) 3643–3657.
- [12] B. Yang, Z. Peng, Fuzzy cognitive map and a mining methodology based on multi-relational data resources, *Fuzzy Information and Engineering* 1 (2009) 357–366.
- [13] J.A. Dickerson, B. Kosko, *Virtual Worlds in Fuzzy Cognitive Maps*, Prentice-Hall, Englewood Cliffs, NJ, 1997.
- [14] E. Papageorgiou, P. Spyridonos, D. Glotsos, C. Stylios, P. Ravazoula, G. Nikiforidis, P. Groumos, Brain tumor characterization using the soft computing technique of fuzzy cognitive maps, *Applied Soft Computing* 8 (2008) 820–828.
- [15] C. Stylios, V. Georgopoulos, G. Malandraki, S. Chouliara, Fuzzy cognitive map architectures for medical decision support systems, *Applied Soft Computing* 8 (2008) 1243–1251.
- [16] A. Kannappan, A. Tamilarasi, E. Papageorgiou, Analyzing the performance of fuzzy cognitive maps with non-linear hebbian learning algorithm in predicting autistic disorder, *Expert Systems with Applications* 38 (2011) 1282–1292.
- [17] E.I. Papageorgiou, A new methodology for decisions in medical informatics using fuzzy cognitive maps based on fuzzy rule-extraction techniques, *Applied Soft Computing* 11 (2011) 500–513.

- [18] E.I. Papageorgiou, N. Papandrianos, G. Karagianni, G. Kyriazopoulos, D. Sfyras, A fuzzy inference map approach to cope with uncertainty in modeling medical knowledge and making decisions, *Intelligent Decision Technologies* 5 (2011) 219–235.
- [19] K.E. Parsopoulos, E.I. Papageorgiou, P.P. Groumpos, M.N. Vrahatis, Evolutionary computation techniques for optimizing fuzzy cognitive maps in radiation therapy systems, in: *Lecture Notes in Computer Science*, pp. 402–413.
- [20] W. Wang, C. Cheung, W. Lee, S. Kwok, Self-associated concept mapping for representation, elicitation and inference of knowledge, *Knowledge-Based Systems* 21 (2008) 52–61.
- [21] C. De Maio, G. Fenza, M. Gaeta, V. Loia, F. Orciuoli, A knowledge-based framework for emergency dss, *Knowledge-Based Systems* 24 (2011) 1372–1379.
- [22] H. Fujita, J. Hakura, M. Kurematu, Cognitive modeling in software and relation to human emotional reasoning, in: *Proceedings of the 7th Conference on 7th WSEAS International Conference on Applied Computer Science*, vol. 7, World Scientific and Engineering Academy and Society, pp. 398–408.
- [23] K.C. Lee, H.R. Cho, J.S. Kim, An expert system using an extended and-or graph, *Knowledge-Based Systems* 21 (2008) 38–51.
- [24] J.L. Salmeron, Modelling grey uncertainty with fuzzy grey cognitive maps, *Expert Systems with Applications* 37 (2010) 7581–7588.
- [25] D.K. Iakovidis, E. Papageorgiou, Intuitionistic fuzzy cognitive maps for medical decision making, *IEEE Transactions on Information Technology in Biomedicine* 15 (2011) 100–107.
- [26] F. Smarandache, Definitions derived from neutrosophics, *Multiple Valued Logic: An International Journal* 8 (2002) 591–603.
- [27] W. Vasantha Kandasamy, F. Smarandache, Fuzzy cognitive maps and neutrosophic cognitive maps, 2003.
- [28] A.P. Dempster, Upper and lower probabilities induced by a multi-valued mapping, *Annals of Mathematics and Statistics* 38 (1967) 325–339.
- [29] Y. Deng, Y. Chen, Y. Zhang, S. Mahadevan, Fuzzy dijkstra algorithm for shortest path problem under uncertain environment, *Applied Soft Computing* 12 (2011) 1231–1237.
- [30] Y. Liu, Y. Jiang, X. Liu, S. Yang, Csmc: a combination strategy for multi-class classification based on multiple association rules, *Knowledge-Based Systems* 21 (2008) 786–793.
- [31] G. Shafer, *A Mathematical Theory of Evidence*, Princeton University Press, Princeton, 1976.
- [32] Z. Su, P. Wang, J. Shen, X. Yu, Z. Lv, L. Lu, Multi-model strategy based evidential soft sensor model for predicting evaluation of variables with uncertainty, *Applied Soft Computing* 11 (2011) 2595–2610.
- [33] Y. Deng, R. Sadiq, W. Jiang, S. Tesfamariam, Risk analysis in a linguistic environment: a fuzzy evidential reasoning-based approach, *Expert Systems with Applications* 38 (2011) 15438–15446.
- [34] Y. Deng, W.K. Shi, Z.F. Zhu, Q. Li, Combining belief functions based on distance of evidence, *Decision Support Systems* 38 (2004) 489–493.
- [35] Y. Deng, F.T.S. Chan, Y. Wu, D. Wang, A new linguistic mcdm method based on multiple-criterion data fusion, *Expert Systems with Applications* 38 (2011) 9854–9861.
- [36] Y. Deng, F.T.S. Chan, A new fuzzy dempster mcdm method and its application in supplier selection, *Expert Systems with Applications* 38 (2011) 6985–6993.
- [37] R. Sadiq, Y. Kleiner, B.B. Rajani, Fuzzy cognitive maps for decision support to maintain water quality in ageing water mains, in: *4th International Conference on Decision-Making in Urban and Civil Engineering*, 2004, pp. 1–10.
- [38] R. Sadiq, Y. Kleiner, B. Rajani, Estimating risk of contaminant intrusion in water distribution networks using dempstercschafer theory of evidence, *Civil Engineering and Environmental System* 23 (2006) 129–141.
- [39] R. Sadiq, Y. Kleiner, B. Rajani, Water quality failures in distribution networks c risk analysis using fuzzy logic and evidential reasoning, *Risk Analysis* 27 (2007) 1381–1394.
- [40] H. Altınçay, Ensembling evidential k -nearest neighbor classifiers through multi-modal perturbation, *Applied Soft Computing* 7 (2007) 1072–1083.
- [41] R. Jones, A. Lowe, M. Harrison, A framework for intelligent medical diagnosis using the theory of evidence, *Knowledge-Based Systems* 15 (2002) 77–84.
- [42] R. Axelrod, *Structure of Decision: The Cognitive Maps of Political Elites*, Prentice-Hall, Upper Saddle River, NJ, 1976.
- [43] B. Kosko, *Fuzzy Engineering*, Prentice-Hall, Upper Saddle River, NJ, 1997.
- [44] Y.M. Wang, J.B. Yang, D.L. Xu, Environmental impact assessment using the evidential reasoning approach, *European Journal of Operational Research* 174 (2006) 1885–1913.
- [45] L. Dymova, P. Sevastjanov, An interpretation of intuitionistic fuzzy sets in terms of evidence theory: decision making aspect, *Knowledge-Based Systems* 23 (2010) 772–782.
- [46] L. Dymova, P. Sevastianov, P. Bartosiewicz, A new approach to the rule-base evidential reasoning: stock trading expert system application, *Expert Systems with Applications* 37 (2010) 5564–5576.
- [47] L.D. Mas, R.M. Salinas, F.J.M. Cuevas, R.M. Carnicer, Shape from silhouette using dempster-shafer theory, *Pattern Recognition* 43 (2010) 2119–2131.
- [48] C. Kalloniatis, P. Belsis, S. Gritzalis, A soft computing approach for privacy requirements engineering: the pris framework, *Applied Soft Computing* 11 (2011) 4341–4348.
- [49] B. Reddy, O. Basir, Concept-based evidential reasoning for multimodal fusion in human-computer interaction, *Applied Soft Computing* 10 (2010) 567–577.
- [50] Y. Zhang, X. Deng, W. Jiang, Y. Deng, Assessment of e-commerce security using ahp and evidential reasoning, *Expert Systems with Applications* 39 (2012) 3611–3623.
- [51] G. Liu, Rough set theory based on two universal sets and its applications, *Knowledge-Based Systems* 23 (2010) 110–115.
- [52] Z. Xiao, X. Yang, Y. Pang, X. Dang, The prediction for listed companies' financial distress by using multiple prediction methods with rough set and dempster-shafer evidence theory, *Knowledge-Based Systems* (2011).
- [53] J.B. Yang, Y.M. Wang, D.L. Xu, K.S. Chin, The evidential reasoning approach for MADA under both probabilistic and fuzzy uncertainties, *European Journal of Operational Research* 171 (2006) 309–343.
- [54] Y.M. Wang, J.B. Yang, D.L. Xu, K.S. Chin, The evidential reasoning approach for multiple attribute decision analysis using interval belief degrees, *European Journal of Operational Research* 175 (2006) 35–66.
- [55] D.L. Xu, J.B. Yang, Y.M. Wang, The evidential reasoning approach for multi-attribute decision analysis under interval uncertainty, *European Journal of Operational Research* 174 (2006) 1914–1943.
- [56] H. Guo, W. Shi, Y. Deng, Evaluating sensor reliability in classification problems based on evidence theory, *IEEE Transactions on Systems Man and Cybernetics Part B-Cybernetics* 36 (2006) 970–981.
- [57] Y. Deng, W. Jiang, R. Sadiq, Modeling contaminant intrusion in water distribution networks: a new similarity-based dst method, *Expert Systems with Applications* 38 (2011) 571–578.
- [58] J. Liu, F.T.S. Chan, Y. Li, Y.J. Zhang, Y. Deng, A new optimal consensus method with minimum cost in fuzzy group decision, *Knowledge-Based Systems* (2012), <http://dx.doi.org/10.1016/j.knosys.2012.04.015>.
- [59] F. voorbraak, On the justification of dempster's rule of combination, *Artificial Intelligence* 48 (1991) 171–197.
- [60] Y. Boutalis, T.L. Kottas, M. Christodoulou, Adaptive estimation of fuzzy cognitive maps with proven stability and parameter convergence, *IEEE Transaction on Fuzzy Systems* 17 (2009) 874–889.